



BDC EPOXY SYSTEMS

SUBJECT: USDA ACCEPTABLE EPOXY

To Whom It May Concern:

The following products meet the performance requirements of the U.S.D.A. as a concrete sealer and topcoat for floors or walls:

Urethanes: BDC 9500 CRU, BDC 9510 CRU, BDC 9600 Water Base CRU, BDC 9700

Polyurea, BDC 70-30 Aliphatic Urethane, BDC 70-45 Aliphatic Urethane

Epoxies: BDC Vapor Seal, BDC 1200, BDC 3100, BDC 3300, BDC 3770, BDC 3798

These products are manufactured and supplied by B. D. Classic Enterprises, Inc. at 12903 Sunshine Avenue, Santa Fe Springs, CA 90670.

These products are suitable and appropriate as concrete coatings when used according to our label instructions and in accordance with the specifications to be offered in this letter. Their use will not result in the adulterations of any food products when used and applied as we, the manufacturer, stipulate.

These products will stand up to rigorous cleaning and dampness and are grease and acid resistant. They are impervious to moisture and contain no known carcinogens, mutagens or tetragens classified as hazardous substances. They are not pesticides nor do they have any known pesticide characteristics. If necessary, we are prepared to supply the federal safety and inspector service with a complete chemical list of the materials used to manufacture these products.

These products should be applied when the temperature of ambient and surface to be coated is 65°F or above. For U.S.D.A. performance, all coats of these products should be allowed to cure at temperatures of 65°F or above.

Apply urethanes at a rate of 275-500 square feet per gallon depending on substrate or between 3-6 mils wet film thickness.

Apply epoxies at the rate of 200-350 square feet per gallon depending on substrate or between 4.5-8 mils wet film thickness.

A copy of this letter should be tendered to the applicator and also for your files.

If you have any questions, please call or fax me.

Yours truly,

**FRED BENSON
President**