

Material Safety Data Sheet

24 Hour EMERGENCY ASSISTANCE			GENERAL MSDS ASSISTANCE
CHEMTREC: (800) 424-9300			B.D. CLASSIC (562) 944-6177
ACUTE HEALTH→2	FIRE→1	REACTIVITY→0	HAZARD RATING→ LEAST - 0 SLIGHT - 1 MODERATE - 2 HIGH - 3 EXTREME - 4
* For acute and chronic health effects refer to the discussion in Section III			

SECTION I	NAME
-----------	------

PRODUCT :BDC 3770P Pigmented - RESIN A
CHEMICAL NAME :MODIFIED BISPHENOL F - EPOXY RESIN
CHEMICAL FAMILY :EPOXY RESIN

SECTION II	PRODUCT/INGREDIENT
------------	--------------------

NO.	COMPOSITION	CAS NUMBER	PERCENT
1	Bisphenol F – Epoxy Resin	9003-36-5	70-100%
2	Titanium Dioxide	13463-67-7	2-30%
3	PROPRIETARY INGREDIENTS		<15%

SECTION III	HAZARDS IDENTIFICATION
-------------	------------------------

THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200). THIS MATERIAL IS CONSIDERED HAZARDOUS.

FORM: LIQUID

EMERGENCY OVERVIEW: WARNING! CAUSES EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. Do not breathe vapor or mist. Do not get on skin or clothing. Avoid contact with eyes. Wash thoroughly after handling.

SECTION V	FIRST AID PROCEDURES
-----------	----------------------

EYE CONTACT

Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

SKIN CONTACT

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

INHALATION

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

INGESTION

Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

NOTE TO PHYSICIAN

No specific treatment. Treat symptomatically. Call medical doctor or poison control center immediately if large quantities have been ingested

SECTION VI**HANDLING AND STORAGE**

HANDLING: PUT ON APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. EATING, DRINKING AND SMOKING SHOULD BE PROHIBITED IN AREAS WHERE THIS MATERIAL IS HANDLED, STORED AND PROCESSED. WORKERS SHOULD WASH HANDS AND FACE BEFORE EATING, DRINKING AND SMOKING. PERSONS WITH A HISTORY OF SKIN SENSITIZATION PROBLEMS SHOULD NOT BE EMPLOYED IN ANY PROCESS IN WHICH THIS PRODUCT IS USED. DO NOT GET IN EYES OR ON SKIN OR CLOTHING. DO NOT BREATHE VAPOR OR MIST. DO NOT INGEST. USE ONLY WITH ADEQUATE VENTILATION. WEAR APPROPRIATE RESPIRATOR WHEN VENTILATION IS INADEQUATE. KEEP IN THE ORIGINAL CONTAINER OR AN APPROVED ALTERNATIVE MADE FROM A COMPATIBLE MATERIAL, KEPT TIGHTLY CLOSED WHEN NOT IN USE. DO NOT REUSE CONTAINER.

STORAGE: STORE IN ACCORDANCE WITH LOCAL REGULATIONS. STORE IN ORIGINAL CONTAINER PROTECTED FROM DIRECT SUNLIGHT IN A DRY, COOL AND WELL-VENTILATED AREA, AWAY FROM INCOMPATIBLE MATERIALS AND FOOD AND DRINK. KEEP CONTAINER TIGHTLY CLOSED AND SEALED UNTIL READY FOR USE. CONTAINERS THAT HAVE BEEN OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE. DO NOT STORE IN UNLABELED CONTAINERS. USE APPROPRIATE CONTAINMENT TO AVOID ENVIRONMENTAL CONTAMINATION. NOTE: THIS RESIN MAY BE HANDLED, SHIPPED AND STORED AT ELEVATED TEMPERATURE IN BULK.

SECTION VII**PHYSICAL DATA**

FORM:	LIQUID
FLASH POINT:	Closed cup: >200°C (>392°F) [EC A.9 Flash-Point (closed cup)]
BOILING POINT:	>200°C (>392°F)
COLOR:	OPAQUE
SOLUBILITY:	SLIGHTLY
SPECIFIC GRAVITY:	1.2
VAPOR PRESSURE:	0.082 kPa (0.615 mm Hg) (20°C)

SECTION VIII**FIRE AND EXPLOSION HAZARDS**

FLASH POINT: Closed cup: >200°C (>392°F) [EC A.9 Flash-Point (closed cup)]
 Hazardous thermal decomposition products: No specific Data

EXTINGUISHING MEDIA:

SUITABLE: Use an extinguishing agent suitable for the surrounding fire.

NOT SUITABLE: None known

SPECIAL EXPOSURE HAZARDS: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION IX	REACTIVITY
-------------------	-------------------

STABILITY: STABLE. UNDER NORMAL CONDITIONS OF STORAGE AND USE, HAZARDOUS REACTIONS WILL NOT OCCUR.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS OF STORAGE AND USE.

CONDITIONS AND MATERIALS TO AVOID:

NO SPECIFIC DATA

HAZARDOUS DECOMPOSITION PRODUCTS

UNDER NORMAL CONDITIONS OF STORAGE AND USE, HAZARDOUS DECOMPOSITION PRODUCTS SHOULD NOT BE PRODUCED.

SECTION X	TOXICOLOGICAL INFORMATION
------------------	----------------------------------

POTENTIAL ACUTE HEALTH EFFECTS:

- Inhalation:** No known significant effects or critical hazards
- Ingestion:** No known significant effects or critical hazards
- Skin:** Irritating to skin. May cause sensitization by skin contact
- Eyes:** Irritating to eyes.

POTENTIAL CHRONIC HEALTH EFFECTS:

- Chronic effects:** Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Target Organs:** Not available.
- Carcinogenicity:** No known significant effects or critical hazards.
- Mutagenicity:** No known significant effects or critical hazards.
- Teratogenicity:** No known significant effects or critical hazards.
- Fertility Effects:** No known significant effects or critical hazards.
- Development Effects:** No known significant effects or critical hazards.
- Medical conditions aggravated by overexposure:** Pre Existing skin disorders may be aggravated by over-exposure to this product

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	DOSE	EXPOSURE
Bisphenol F – Epoxy Resin	LD50 Dermal	Rat-Male, Female	>2000 mg/kg	-

CHRONIC TOXICITY: PRODUCT/INGREDIENT NAME	LD50 ORAL	SPECIES	DOSE	EXPOSURE
Bisphenol F – Epoxy Resin	Sub-chronic, NOAEL oral	Rat-Male, Female	>5000 mg/kg	-
		Rat-Male, Female	250 mg/kg	13 weeks: 7 days/week

MUTAGENICITY: PRODUCT/INGREDIENT NAME	TEST	EXPERIMENT	RESULT
Bisphenol F-Epoxy Resin	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria metabolic activation: +/-	Positive
	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Mammalian-Human Cell: Somatic Metabolic activation: +/-	Positive
	OECD 473 <i>In vitro</i> Mammalian Chromosomal Aberration Test	Experiment: In vitro Subject: Mammalian-Human Cell: Somatic Metabolic activation: +/-	Positive
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
	OECD 486 Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells <i>in vivo</i>	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

SENSITIZER: PRODUCT/INGREDIENT NAME	ROUTE OF EXPOSURE	SPECIES	RESULT
Bisphenol F-Epoxy Resin	Skin	Mouse	sensitizing

TETRAGENICITY: PRODUCT/INGREDIENT NAME	MATERNAL TOXICITY	FERTILITY	DEVELOPMENT TOXIN	SPECIES	DOSE	EXPOSURE
Bisphenol F-Epoxy Resin	Negative	Negative	Negative	Rat Male, Female	- Oral: 540 mg/kg NOEL	238 days; 7 days per week

REPRODUCTIVE TOXICITY: PRODUCT/INGREDIENT NAME	RESULT	SPECIES	DOSE	EXPOSURE
Bisphenol F-Epoxy Resin	Negative – dermal	Rabbit – female	>300 mg/kg Noel	13 days: 6 hrs per day

SECTION X	ECOLOGICAL INFORMATION
------------------	-------------------------------

Environmental Effects: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Not readily biodegradable. This product shows a high bioaccumulation potential. Water polluting material. May be harmful to the environment if released in large quantities

Aquatic Ecotoxicity:

PRODUCT/INGREDIENT NAME	TEST	RESULT	SPECIES	EXPOSURE
Bisphenol F-Epoxy Resin	OECD 201 Alga, Growth Inhibition test	Acute EC50 1.8 mg/L Fresh water	Algae	72 hours Static
	OECD OECD 202: Part I (Daphnia sp., Acute Immobilisation test)	Acute EC50 1.6 mg/L Fresh water	Daphnia	48 hours Static
	-	Acute IC50 >100 mg/L Fresh water	Bacteria	3 hours Static
	OECD 203 Fish, Acute Toxicity	Acute LC50 0.55 mg/L Fresh water	Fish	96 hours Semistatic
	OECD 211 <i>Daphnia Magna</i> Reproduction	Chronic NOEC 0.3 mg/L Fresh water	Daphnia	21 days Semistatic

Biodegradability

PRODUCT/INGREDIENT NAME	TEST	RESULT	DOSE	INOCULUM
Bisphenol F-Epoxy Resin	EU	0 % - Not readily - 28 days	3 mg/L Oxygen consumption	Activated sludge

Other Ecological Information: Not Determined

PRODUCT/INGREDIENT NAME	AQUATIC HALF-LIFE	PHOTOLYSIS	BIODEGRADABILITY
Bisphenol F-Epoxy Resin	-	-	Not readily

Bioaccumulative Potential:

PRODUCT/INGREDIENT NAME	LogPow	BCF	Potential
Bisphenol F-Epoxy Resin	2.7-3.6	-	high

Other Adverse Effects: No known significant effects or critical hazards

PBT: Not applicable

SECTION X**EMPLOYEE PROTECTION**

CONSULT LOCAL AUTHORITIES FOR ACCEPTABLE EXPOSURE LIMITS.

RECOMMENDED MONITORING PROCEDURES: IF THIS PRODUCT CONTAINS INGREDIENTS WITH EXPOSURE LIMITS, PERSONAL WORKPLACE ATMOSPHERE OR BIOLOGICAL MONITORING MAY BE REQUIRED TO DETERMINE THE EFFECTIVENESS OF THE VENTILATION OR OTHER CONTROL MEASURES AND/OR THE NECESSITY TO USE RESPIRATORY PROTECTIVE EQUIPMENT.

ENGINEERING MEASURES: USE ONLY WITH ADEQUATE VENTILATION. IF USER OPERATIONS GENERATE DUST, FUMES, GAS, VAPOR OR MIST, USE PROCESS ENCLOSURES, LOCAL EXHAUST

VENTILATION OR OTHER ENGINEERING CONTROLS TO KEEP WORKER EXPOSURE TO AIRBORNE CONTAMINANTS BELOW ANY RECOMMENDED OR STATUTORY LIMITS.

HYGIENE MEASURES: WASH HANDS, FOREARMS AND FACE THOROUGHLY AFTER HANDLING CHEMICAL PRODUCTS, BEFORE EATING, SMOKING AND USING THE LAVATORY AND AT THE END OF THE WORKING PERIOD. APPROPRIATE TECHNIQUES SHOULD BE USED TO REMOVE POTENTIALLY CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE REUSING. ENSURE THAT EYEWASH STATIONS AND SAFETY SHOWERS ARE CLOSE TO THE WORKSTATION LOCATION.

RESPIRATORY PROTECTION: USE A PROPERLY FITTED, AIR-PURIFYING OR AIR-FED RESPIRATOR COMPLYING WITH AN APPROVED STANDARD IF A RISK ASSESSMENT INDICATES THIS IS NECESSARY. RESPIRATOR SELECTION MUST BE BASED ON KNOWN OR ANTICIPATED EXPOSURE LEVELS, THE HAZARDS OF THE PRODUCT AND THE SAFE WORKING LIMITS OF THE SELECTED RESPIRATOR.

EYES: SAFETY EYEWEAR COMPLYING WITH AN APPROVED STANDARD SHOULD BE USED WHEN A RISK ASSESSMENT INDICATES THIS IS NECESSARY TO AVOID EXPOSURE TO LIQUID SPLASHES, MISTS, GASES OR DUSTS.

SKIN: PERSONAL PROTECTIVE EQUIPMENT FOR THE BODY SHOULD BE SELECTED BASED ON THE TASK BEING PERFORMED AND THE RISKS INVOLVED AND SHOULD BE APPROVED BY A SPECIALIST BEFORE HANDLING THIS PRODUCT.

ENVIRONMENTAL EXPOSURE CONTROLS: EMISSIONS FROM VENTILATION OR WORK PROCESS EQUIPMENT SHOULD BE CHECKED TO ENSURE THEY COMPLY WITH THE REQUIREMENTS OF ENVIRONMENTAL PROTECTION LEGISLATION. IN SOME CASES, FUME SCRUBBERS, FILTERS, OR ENGINEERING MODIFICATIONS TO THE PROCESS EQUIPMENT WILL BE NECESSARY TO REDUCE EMISSIONS TO ACCEPTABLE LEVELS.

SECTION XI**ENVIRONMENTAL PROTECTION/ ACCIDENTAL RELEASE MEASURES**

PERSONAL PRECAUTIONS: NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. EVACUATE SURROUNDING AREAS. KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING. DO NOT TOUCH OR WALK THROUGH SPILLED MATERIAL. AVOID BREATHING VAPOR OR MIST. PROVIDE ADEQUATE VENTILATION. WEAR APPROPRIATE RESPIRATOR WHEN VENTILATION IS INADEQUATE. PUT ON APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT.

ENVIRONMENTAL PRECAUTIONS: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

METHODS FOR CLEANING UP: STOP LEAK IF WITHOUT RISK. MOVE CONTAINERS FROM SPILL AREA. APPROACH RELEASE FROM UPWIND. PREVENT ENTRY INTO SEWERS, WATER COURSES, BASEMENTS OR CONFINED AREAS. WASH SPILLAGES INTO AN EFFLUENT TREATMENT PLANT OR PROCEED AS FOLLOWS. CONTAIN AND COLLECT SPILLAGE WITH NON-COMBUSTIBLE, ABSORBENT MATERIAL E.G. SAND, EARTH, VERMICULITE OR DIATOMACEOUS EARTH AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS. DISPOSE OF VIA A LICENSED WASTE DISPOSAL CONTRACTOR. CONTAMINATED ABSORBENT MATERIAL MAY POSE THE SAME HAZARD AS THE SPILLED PRODUCT.

WASTE DISPOSAL: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION XII**SPECIAL PRECAUTIONS**

STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES. HANDLE IN ACCORDANCE WITH THE POTENTIAL HAZARD OF THE CURING AGENT USED.

WARNING. POTENTIAL SENSITIZER. CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED, CAN CONTAIN HAZARDOUS PRODUCT RESIDUES. MINIMIZE ALL CONTACT WITH MATERIAL. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, APPLYING COSMETICS OR USING TOILET FACILITIES. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE. CONTAMINATED LEATHER ARTICLES, INCLUDING SHOES CANNOT BE DECONTAMINATED AND SHOULD BE DESTROYED TO PREVENT REUSE.

HEATING THIS RESIN ABOVE 300 DEG F IN THE PRESENCE OF AIR MAY CAUSE SLOW OXIDATIVE DECOMPOSITION ABOVE 500 DEG F, POLYMERIZATION MAY OCCUR. SOME CURING AGENTS, E.G., ALIPHATIC POLYAMINES CAN PRODUCE EXOTHERMIC REACTIONS WHICH IN LARGE MASSES CAN CAUSE RUNAWAY POLYMERIZATION AND CHARRING OF THE REACTANTS. FUMES AND VAPORS FROM THESE THERMAL AND CHEMICAL DECOMPOSITIONS VARY WIDELY IN COMPOSITION AND TOXICITY. DO NOT BREATHE FUMES.

USE A NIOSH-APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE. IN ACCORD WITH 20 CFR 1910.134, USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS. IF THIS RESIN IS HANDLED, SHIPPED, OR STORED IN BULK, THE RECOMMENDED PUMPING TEMPERATURE IS 180 DEG F, MAX. TO PREVENT THERMAL BURNS. AVOID SKIN AND EYE CONTACT WITH HOT LIQUID.

SECTION XIII**TRANSPORTATION REQUIREMENTS**

THE DATE PROVIDED IN THIS SECTION IS FOR INFORMATION ONLY AND MAY NOT BE SPECIFIC TO YOUR PACKAGE SIZE OR MODE OF TRANSPORT. YOU WILL NEED TO APPLY THE APPROPRIATE REGULATIONS TO PROPERLY CLASSIFY YOUR SHIPMENT FOR TRANSPORTATION.

DOT CLASSIFICATION

Environmentally hazardous substance, liquid, n.o.s. (bisphenol F-epoxy resin) Marine pollutant
U.N. 3082
CLASS 9

PG III

TDG CLASSIFICATION

Environmentally hazardous substance, liquid, n.o.s. (bisphenol F-epoxy resin) Marine pollutant
U.N. 3082
CLASS 9
PG III

IMDG CLASSIFICATION

Environmentally hazardous substance, liquid, n.o.s. (bisphenol F-epoxy resin) Marine pollutant
U.N. 3082
CLASS 9
PG III
EMERGENCY SCHEDULES (EmS) – F-A, S-F

IATA-DGR CLASSIFICATION

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol F-epoxy resin)
U.N. 3082
CLASS 9
PG III
PASSENGER AND CARGO AIRCRAFT: QUANTITY LIMITATION: 450 L. PACKAGING INSTRUCTIONS: 964
CARGO AIRCRAFT ONLY: QUANTITY LIMITATION: 450 L. PACKAGING INSTRUCTIONS: 964

SECTION XIV OTHER REGULATORY CONTROLS

US REGULATIONS:

HCS CLASSIFICATION: IRRITATING MATERIAL, SENSITIZING MATERIAL

US FEDERAL REGULATIONS: UNITED STATES INVENTORY (TSCA 8b): NOT DETERMINED

SARA 313 SUPPLIER NOTIFICATIONS: NO INGREDIENTS LISTED

SARA 302/304/311/312 EXTREMELY HAZARDOUS SUBSTANCES: NO INGREDIENTS LISTED

IN ACCORDANCE WITH SARA TITLE III, SECTION 313, THE ENVIRONMENTAL DATA SHEET (EDS) SHOULD ALWAYS BE COPIED AND SENT WITH THE MSDS.

CANADA:

WHMIS (CANADA) CLASS D-2B: MATERIAL CAUSING OTHER TOXIC EFFECTS (TOXIC)

CANADIAN LISTS CANADIAN NPRI: NONE REQUIRED

INTERNATIONAL REGULATIONS:

CHEMICAL INVENTORIES

EUROPE INVENTORY – ALL COMPONENTS ARE LISTED OR EXEMPT

AUSTRALIA INVENTORY (AICS) – ALL COMPONENTS ARE LISTED OR EXEMPT

CHINA INVENTORY (IECSC) – ALL COMPONENTS ARE LISTED OR EXEMPT

KOREA INVENTORY (KECI) – ALL COMPONENTS ARE LISTED OR EXEMPT

PHILLIPINES INVENTORY (PICCS) – ALL COMPONENTS ARE LISTED OR EXEMPT
JAPAN INVENTORY (ENCS) – ALL COMPONENTS ARE LISTED OR EXEMPT
UNITED STATES INVENTORY (TSCA 8B) – ALL COMPONENTS ARE LISTED OR EXEMPT
CANADA INVENTORY – ALL COMPONENTS ARE LISTED OR EXEMPT

SECTION XV STATE REGULATORY INFORMATION

STATE REGULATIONS: MASSACHUSETTS RTK SUBSTANCES – NONE REQUIRED
NEW JERSEY RTK HZAZARDOUS SUBSTANCES – NON REQUIRED
PENNSYLVANIA RTK HAZARDOUS SUBSTANCES – NON REQUIRED
CALIFORNIA PROP. 65: WARNING: This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute

SECTION XVI SPECIAL NOTES

HAZARDOUS MATERIAL HEALTH: 2
INFORMATION SYSTEM III FLAMMABILITY: 1
U.S.A. PHYSICAL HAZARDS: 0
CHRONIC:

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, B D CLASSIC MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. B D CLASSIC ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

BE SAFE
READ OUR PRODUCT SAFETY INFORMATION...AND PASS IT ON
(PRODUCT LIABILITY REQUIRES IT)