

# STONE GLAZE Clear Lacquer Sealer

High Gloss Finish For Concrete & Masonry

**COVERAGE:** Up to 400 ft.<sup>2</sup> per gallon on a smooth surface and between 200-300 ft.<sup>2</sup> per gallon on a rough surface.

**SURFACE PREPARATION:** Surface must be dry and free of oil, grease, curing agents, dirt, dust or other foreign material. Prepare surface by sanding, grinding, water blasting or shot blasting to achieve a clean, porous and uniform surface that will allow product to soak in and bond permanently. (The surface profile should resemble 80-100 grit sandpaper.) Muriatic Acid (blended 1:4 with water) may be used to etch smooth concrete. Neutralize residual acid with a solution of baking soda (1 lb. per gallon of water). Scrub surface and rinse several times. Please use caution when working with acid. Read and follow all warnings and instructions on label. Clean surface entirely with TSP and rinse completely with water several times. New concrete must be at least 28 days old.

**THINNING:** 10-20% Acetone may be added to thin material for better absorption, increased coverage, longer working time and to minimize bubbling. Acetone is flammable. See acetone label precautions before using. Do not expose to open flame or sparks. Extinguish pilot lights or any other flame in the working area.

**APPLICATION:** Stone Glaze is ready to use from the can and requires no mixing or stirring. Apply 1-2 light even coats (depending on porosity of surface) of Stone Glaze with a natural bristle brush or low pressure/airless sprayer (with metal or teflon tip). Brush or spray product as thin as possible. Avoid puddling as material will turn white and possibly bubble up. REMEMBER TO TURN OFF SPRINKLERS FOR THE FIRST 48 HOURS. Diluting slightly with acetone and applying thin coats will help avoid streaks in direct sun.

**DRYING TIME:** Stone Glaze dries very fast and can be recoated in as soon as 30 to 60 minutes. Foot traffic may be permitted after 4-8 hours. Allow 72 hours for vehicle traffic and before placing heavy objects on the surface.

**CLEAN UP:** Uncured material can be removed with acetone or similar solvent.

**LIMITATIONS:**

- Do not apply when ambient or surface temperatures are below 45°F or above 95°F.

- Do not apply more than 2 thin coats.

- Do not apply if rain is in the near forecast (48 hours). Rain may cause Stone Glaze to whiten after new application.

**WARNING:** Flammable liquid and vapor. Peroxide former. High vapor concentrations may cause irritation of the eyes, skin, dizziness, drowsiness and lung damage. DO NOT TAKE INTERNALLY. Extinguish all flames, pilot lights and electric motors until all vapors are gone and the coating is hard. The vapor is harmful and flammable. DO NOT SMOKE. Use only with adequate ventilation and/or appropriate cartridge type respirator. Avoid contact with skin and wear protective gloves. Read material Safety Data Sheets before using. May cause injury to skin following prolonged or repeated contact. Absorption through skin may be harmful. Clean hands thoroughly after use and before smoking or eating. Keep closure tight and container upright to prevent leakage when not in use. Do not transfer contents to bottles or other unlabeled containers. In case of spillage, absorb, sweep up, and place in a proper waste disposal container. In case of fire, use foam, dry chemical or CO<sub>2</sub>. Flush area with water.

**FIRST AID: Internal:** If swallowed, do not induce vomiting. Call physician immediately. **Eyes:** Immediately flush with plenty of water for 15 minutes forcibly holding eye lids open and call a physician. **External:** Wipe off skin with thinner, then immediately wash thoroughly with soap and water. Remove contaminated clothing. **Inhalation:** remove to fresh air. If not breathing, give artificial respiration. Call a physician.

### Protects and Beautifies:

- Exposed Aggregate
- Stamped Concrete
- Colored Concrete
- Porous Brick
- Unglazed Tile
- Natural Slate & Stone
- Flagstone



# STONE GLAZE

## CLEAR LACQUER SEALER

High Gloss Finish For  
Concrete & Masonry

A clear, high-gloss finish designed for interior and exterior use. It brings life, luster, and a fresh "wet" appearance to patios, driveways, garage floors, and other surfaces.

**WARNING:** Possible slipperiness. Be aware that oil, water, mud or other materials on a walkway sealed with Stone glaze may make the surface slippery and therefore, potentially dangerous.

**CAUTION:** DO NOT TAKE INTERNALLY. CLOSE THE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN NON-PHOTOCHEMICALLY REACTIVE (LESS THAN 4%)



Manufactured by: B. D. Classic Enterprises, Inc.  
12903 Sunshine Avenue, Santa Fe Springs, CA 90670-0445

Pho. 800-543-8551  
Fax 562-946-8572

Bar Code

#1530F  
Stone Glaze

1 Gallon  
(128oz. / 3.785L)