

# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

---

Revision date: 2015/08/14

### 1. Identification

**Product identifier used on the label**

**BDC 9500-250VOC - PART B - RESIN**

**Recommended use of the chemical and restriction on use:**

**Industrial Maintenance Coating, Waterproofing/Concrete Masonry Sealer**

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:

B.D. Classic Enterprises

P.O. 2445

Santa Fe Springs, CA 90670

562-944-6177

**Emergency telephone number**

CHEMTREC: 1-800-424-9300

**Other means of identification**

Chemical family: Modified Polyester Resin Solution

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200**

**Classification of the product**

Flammable liquid, Category 3

Reproductive toxicity, Category 1B

Label Elements

Pictogram:



Signal Word: Danger

Hazard Statement:

Flammable

---

# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

---

Revision date: 2015/08/14

Harmful if inhaled.  
Toxic if inhaled.  
May cause respiratory irritation.  
May damage fertility or the unborn child.  
May cause respiratory irritation.  
Causes serious eye irritation  
May cause drowsiness or dizziness

#### Precautionary Statements (Prevention):

Wear eye/face protection.  
Wear protective gloves.  
Use only outdoors or in a well-ventilated area.  
Do not breathe dust/gas/mist/vapors.  
Avoid release to the environment.  
Contaminated work clothing should not be allowed out of the workplace.  
Wash with plenty of water and soap thoroughly after handling  
Keep away from heat, hot surfaces, open flames, sparks – No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical, lighting, ventilating equipment  
Use only non-sparking tools  
Take Precautionary measures against static discharge

#### Precautionary Statements (Response):

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF ON SKIN (or hair): Wash with plenty of soap and water.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry chemical poser, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>) for extinction

#### Precautionary Statements (Storage):

Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Keep cool

#### Precautionary Statements (Disposal):

Dispose of contents/container to hazardous or special waste collection point.

#### **Hazards not otherwise classified**

No specific dangers known

#### **Supplemental information:**

Potential Health Effects:

Due to the presence of the solvent: Prolonged or repeated skin contact may cause defatting resulting in drying, redness and rash. Contains high molecular weight polymer(s). Effects due to processing releases: Irritating to eyes, respiratory system and skin. Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness, (severity of effects depends on extent of exposure). Use with local exhaust ventilation. Wear protective clothing. Wear full face shield if splashing hazard exists.

---

### 3. Composition / Information on Ingredients

# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

Revision date: 2015/08/14

Components	CAS Number	Concentration (Weight)
Polyester Resin Solution	Proprietary	25-60 %
Propylene Glycol Monomethyl Ether Acetate	108-65-6	10-35 %
Benzene, 1-Chloro-4(trifluoromethyl)	98-56-6	10-25 %
Proprietary	Proprietary	< 20 %

### 4. First-Aid Measures

#### Description of first aid measures

**General advice:**

Immediately remove contaminated clothing.

**If inhaled:**

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

**If on skin:**

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

**If in eyes:**

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Seek medical attention.

**If swallowed:**

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

**Most important symptoms and effects, both acute and delayed:**

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote, administer corticosteroid dose aerosol to prevent pulmonary odema.

### 5. Fire-Fighting Measures

**Extinguishing media**

Suitable extinguishing media: Preferable: Alcohol resistant foam. Water spray, CO2

Unsuitable extinguishing media: Solid water jet ineffective as extinguishing medium

**Special hazards arising from the substance or mixture**

Hazards during fire-fighting: harmful vapors

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

**Advice for fire-fighters**

Protective equipment for fire-fighting:

# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

---

Revision date: 2015/08/14

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

### Fire Hazard:

Highly flammable. Gas/vapour flammable with air within explosion limits. INDIRECT FIRE HAZARD. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard"

### Explosion Hazard:

DIRECT EXPLOSION HAZARD. Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. Heat may cause pressure rise in tanks/drums: explosion risk. May be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

---

## 7. Handling and Storage

### General information on handling:

Do not taste or swallow.

Do not get in eyes, on skin, or on clothing.

Do not breathe vapor or mist.

Keep away from heat, sparks and flames.

No smoking.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Check that all equipment is properly grounded and installed to satisfy electrical classification requirements.

Container hazardous when empty.

Follow label warnings even after container is emptied.

RESIDUAL VAPORS MAY EXPLODE ON IGNITION.

DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR THIS CONTAINER.

Improper disposal or reuse of this container may be dangerous and/or illegal.

Emptied container retains vapor and product residue.

### Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place away

# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

---

Revision date: 2015/08/14

from heat sources, direct sunlight.

Storage stability:

May react with oxygen to form peroxides

Storage Incompatibility – General

Store separate from:

Strong acids, Strong oxidizing agents, Strong Bases, Reducing Agents.

Storage Temperature: 15 – 20 C

Storage Area:

Store in a cool area. Keep out of direct sunlight. Store in a dry area. Store in a dark area. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing. Meet the legal requirements.

Special rules on packaging:

SPECIAL REQUIREMENTS: closing with pressure relief valve. clean. opaque. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.

Packaging materials:

SUITABLE MATERIAL: steel. stainless steel. carbon steel. aluminium. iron. copper. nickel. bronze. glass.

MATERIAL TO AVOID: synthetic material

---

## 8. Exposure Controls/Personal Protection

### Engineering Measures

Provide readily accessible eye wash stations and safety showers.

Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits

### Personal protective equipment

#### Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapor/particulate respirator. Do not exceed the maximum use concentration for the respirator face piece/cartridge combination. For emergency or non-routine, high exposure situations, use a NIOSH-certified full face piece pressure demand self-contained breathing apparatus (SCBA) or a full face piece pressure demand supplied-air respirator (SAR) with escape provisions.

#### Hand protection:

Chemical resistant protective gloves

#### Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists

#### General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Avoid inhalation of mists. Contact with eyes and skin must be avoided.

Occupational Exposure limit(s)

# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

Revision date: 2015/08/14

2-Propanol, 1-methoxy-, acetate (108-65-6)	Time Weighted Average (TWA):	50 ppm (listed)
--	------------------------------	-----------------

---

### 9. Physical and Chemical Properties

Form:	liquid
Odor:	Solvent, sweet
Color:	Clear-Amber, Cloudy
pH value:	N/A
Melting point:	No data available
Boiling point:	290 °F
Flash point:	115 °F Closed Cup
Flammability:	Flammable
Lower explosion limit:	Not applicable
Upper explosion limit:	Not applicable
Vapor pressure:	< 0.03 hPa at 20 °C
Density:	1.15 g/cm <sup>3</sup> at 20 °C
Viscosity, Dynamic	500-1000 CPS
Solubility in Water	Hydrolyzes
Evaporation rate:	Not determined
Volatile Organic Compounds:	< 250 g/l (per AQMD)

---

### 10. Stability and Reactivity

Corrosion to metals:  
Corrosion effect on metals are not anticipated

Chemical Stability:  
Stable under normal conditions.

Conditions to avoid:  
Avoid moisture. Avoid sources of ignition.

Materials to avoid:  
Strong acids  
Strong oxidizing agents  
Strong bases  
Reducing agents  
May react with oxygen to form peroxides

Hazardous decomposition products:  
Thermal decomposition giving flammable and toxic products:  
Carbon oxides  
Hazardous organic compounds

---

### 11. Toxicological information

Data on this material and/or its components are summarized below.

# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

---

Revision date: 2015/08/14

### Inhalation:

4 h Acute toxicity estimate > 40 mg/l. (vapor)

Data for 2-Propanol, 1-methoxy-, acetate (108-65-6)

### Acute toxicity

#### Oral:

Practically nontoxic. (Rat) LD50 = 6,190 mg/kg.

#### Dermal:

Practically nontoxic. (Rabbit) LD0 > 5,000 mg/kg.

#### Skin Irritation:

Not irritating. (Rabbit) Irritation Index: 0/8. (4 h)

#### Eye Irritation:

Causes mild eye irritation. (Rabbit)

#### Skin Sensitization:

Not a sensitizer. Guinea pig maximization test. (Guinea pig) No skin allergy was observed

### Repeated dose toxicity

Repeated inhalation administration to rat, mouse / affected organ(s): nasal tissues

Subacute oral administration to rat / affected organ(s): adrenal gland / signs: changes in body weight, changes in organ weights

### Genotoxicity

#### Assessment in Vitro:

No genetic changes were observed in laboratory tests using: bacteria, animal cells

### Developmental toxicity

Exposure during pregnancy. Inhalation (rat) / No birth defects were observed.

### Reproductive effects

Reproductive/Developmental Effects Screening Assay. Oral (rat) / No toxicity to reproduction.

### Human experience

#### General:

Can be absorbed through the skin.

### Human experience

#### Inhalation:

Respiratory tract: coughing, shortness of breath.

### Human experience

#### Skin contact:

Skin: irritation, redness. (repeated or prolonged exposure)

### Human experience

#### Eye contact:

Eye: Pain, redness, swelling, tearing.

# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

Revision date: 2015/08/14

---

### 12. Ecological Information

#### Chemical Fate and Pathway

Data on this material and/or its components are summarized below.

#### Data for 2-Propanol, 1-methoxy-, acetate (108-65-6)

##### Biodegradation:

Readily biodegradable. (10 d) biodegradation 83 %

##### Biological Oxygen Demand:

BOD = 0.363 mg/g

##### Octanol Water Partition Coefficient:

log Pow = 1.2 (measured)

#### Ecotoxicology

Data on this material and/or its components are summarized below.

#### Data for 2-Propanol, 1-methoxy-, acetate (108-65-6)

##### Aquatic toxicity data:

Practically nontoxic. *Oryzias latipes* (Orange-red killifish) 96 h LC50 > 100 mg/l

Practically nontoxic. *Oncorhynchus mykiss* (rainbow trout) 96 h LC50 = 134 mg/l

Practically nontoxic. *Pimephales promelas* (fathead minnow) 96 h LC50 = 161 mg/l

##### Aquatic invertebrates:

Practically nontoxic. *Daphnia magna* (Water flea) 48 h EC50 > 500 mg/l

##### Algae:

Practically nontoxic. *Selenastrum capricornutum* 72 h EC50 > 1,000 mg/l

##### Chronic toxicity to aquatic invertebrates:

*Daphnia magna* (Water flea) 21 d NOEC > 100 mg/l

---

### 13. Disposal Considerations

Dispose of in a licensed facility. Do not discharge into waterways or sewer systems without proper authorization.

#### Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

---

### 14. Transport Information

#### Land transport

USDOT

Proper Shipping Name: Resin Solution

Hazard Class or Division: 3

UN/NA Number: 1866

Packaging Group: III

Hazard Label(s): Warning, Flammable Liquid

Hazard Placards(s): Flammable

#### Sea transport

IMDG

Proper Shipping Name: Resin Solution

Hazard Class or Division: 3

UN/NA Number: 1866

Packaging Group: III

Hazard Label(s): Warning, Flammable Liquid

Hazard Placards(s): Flammable



# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

Revision date: 2015/08/14

### Air transport

IATA/ICAO  
 Proper Shipping Name: Resin Solution  
 Hazard Class or Division: 3  
 UN/NA Number: 1866  
 Packaging Group: III  
 Hazard Label(s): Warning, Flammable Liquid  
 Hazard Placards(s): Flammable

## 15. Regulatory Information

EU. EINECS	EINECS	Does not conform
United States TSCA Inventory	TSCA	This product complies with TSCA Inventory requirements. The polymer component(s) is (are) eligible for the amended polymer exemption at 40 CFR Section 723.250.
Canadian Domestic Substances List (DSL)	DSL	This product contains one or several components that are not on the Canadian DSL nor NDSL lists.
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Does not conform
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Does not conform
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Does not conform
Australia Inventory of Chemical Substances (AICS)	AICS	Does not conform

### United States – Federal Regulations

#### **SARA Title III – Section 302 Extremely Hazardous Chemicals:**

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

#### **SARA Title III - Section 311/312 Hazard Categories:**

Fire Hazard, Chronic Health Hazard

#### **SARA Title III – Section 313 Toxic Chemicals:**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) – Reportable Quantity (RQ):**

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

### United States – State Regulations

#### **New Jersey Right to Know**

No components are subject to the New Jersey Right to Know Act.

#### **Pennsylvania Right to Know**

Chemical Name	CAS-No.
saturated polyester resin solution	Proprietary
2-Propanol, 1-methoxy-, acetate	108-65-6

# Safety Data Sheet

## BDC 9500-250VOC – PART B - RESIN

---

Revision date: 2015/08/14

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects

## 16. Other Information

### NFPA Hazard Codes:

Health	:	2
Fire	:	3
Reactivity	:	1
Special	:	0

### SDS Prepared by:

B.D. Classic Enterprises

---

The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication as part of B. D. Classic Enterprises, Inc. Product Safety Program. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information obtained herein. Data sheets are available for all B. D. Classic products. You are urged to obtain data sheets for all B. D. Classic products you buy, process, use or distribute and you are encouraged and requested to advise those who may come in contact with such products of the information contained therein.

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. B. D. Classic does not undertake to furnish advice on such matters.