

SAFETY DATA SHEET

1. Identification

Product Identifier: BDC 70-30 Aliphatic Urethane

Use: Coating Material. For Industrial/Professional use

only.

Manufacturer: BDC Epoxy Systems, Inc

12903 Sunshine Ave

Santa Fe Springs, CA 90670

Phone Number: 562-944-6177

Emergency Phone: CHEMTREC 800-424-9300

Email: info@bdcepoxy.com

2. Hazards Identification

GHS Classification:

Flammable Liquids – Category 2

Acute Toxicity (inhalation) – Category 4

Skin Irritation – Category 2

Eye Irritation – Category 2A

Respiratory Sensitization – Category 1

Skin Sensitization – Category 1

Specific Target Organ Toxicity – Single Exposure Category 3

Hazardous to the Aquatic Environment – Acute Hazard Category 2

Hazardous to the Aquatic Environment – Chronic Hazard Category 2

Label Elements: Danger









Hazard Phrases:

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Phrases:

P210 Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilation, and lightly equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing fumes, vapors, mists or sprays.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, protective clothing, eye protection,

and face protection.

P284 In case of inadequate ventilation, wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse affected areas with water or

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P317 Get medical help.

P319 Get medical help if you feel unwell.

P333+P317 If skin irritation or rash occurs: Get medical help.

P337+P317 If eye irritation persists: Get medical help.

P342+P316 If experiencing respiratory symptoms: Get emergency

medical help immediately.

P362+P364 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local,

regional, and national regulations.

Supplemental Information: This product is highly flammable. Ensure all appropriate bonding and grounding methods are followed.

3. Composition/Information on Ingredients

Chemical Name	CAS#	%
Hexamethylene diisocyanate	28182-81-2	20-30
Acetone	67-64-1	20-30
Parachlorobenzotrifluoride	98-56-6	20-30

Exact concentrations are withheld as trade secret. Other ingredients are not classified as health, physical or environmental hazards, or are present below cut-off/concentrations limits.

4. First-Aid Measures

Eye Contact: Rinse thoroughly with water for at least 15 minutes, holding the eyelids open to be sure the material is washed out. Remove contact lenses if present and easy to do. Get medical attention if irritation develops or persist.

Skin Contact: Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation develops or persists. Launder clothing before re-use. Discard items that cannot be decontaminated.

Inhalation: If inhaled, remove person to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention immediately.

Ingestion: Rinse mouth. Do not induce vomiting. Get medical if you feel unwell.

Most Important Symptoms/Effects: Harmful if inhaled.

Indication of Immediate Medical Attention/Special Treatment: Get immediate medical attention if inhaled.

5. Fire-Fighting Measures



SAFETY DATA SHEET

Extinguishing Media: Use foam, carbon dioxide, water fog or dry

chemical.

Specific Hazards: Highly flammable liquid and vapor.

Special Protective Equipment & Precautions for Fire-Fighters:

Wear positive pressure, self-contained breathing apparatus and full-body protective clothing. Cool fire-exposed containers with water.

6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency

Procedures: Remove all ignition sources. Clear non-emergency personnel from the area. Wear appropriate protective clothing to prevent eye and skin contact and avoid breathing vapors. Ventilate area.

Methods and Materials for Containment and Cleanup: Do not discharge material into waterways. Cover with an inert absorbent material and collect into an appropriate container for disposal. Avoid release to the environment.

7. Handling and Storage

Safe Handling: Obtain, read, and follow instructions before use. Avoid contact with eyes, skin, and clothing. Avoid breathing fumes, vapors, mists or sprays. When using, do not eat, drink, or smoke. Use outdoors or with properly positioned local exhaust ventilation to prevent exposure. Wash thoroughly after handling. Keep container closed when not in use.

Safe Storage: Store indoors at temperatures between 40°F and 95°F. Ground and bond container. Store in original, unopened containers away from incompatible materials, open flames, and high temperatures.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits: For Acetone (CAS 67-64-1):
ACGIH TLV 500 ppm TWA, 750 ppm STEL

Ventilation: Use with properly positioned local exhaust ventilation to prevent exposure and maintain air levels below the occupational exposure limits.

Respiratory Protection: If ventilation is not adequate, use a NIOSH-approved respirator with organic vapor cartridges or supplied air. Respirator selection and use should be based on contaminant type, form, and concentration. For higher exposures or in an emergency, use a supplied-air respirator. Use respirators in accordance with OSHA's Respiratory Protection Standard (29 CFR 1910.134).

Skin Protection: Wear impervious gloves, such as butyl rubber or nitrile rubber.

Eye Protection: Wear chemical safety goggles or face shield.

Other Protective Measures: Wear impervious clothing to prevent skin contact and contamination of personal clothing. An eye wash facility and washing facility should be available in the work area. Follow applicable regulations and good Industrial Hygiene practice.

9. Physical and Chemical Properties

Appearance: Liquid **Odor:** No data available

Odor Threshold: No data available

pH: No data available

Melting Point/Freezing Point: No data available

Boiling Point: No data available

Flash Point: <20°F

Evap. Rate: No data available
Flamm. Limits: No data available
Vapor Pressure: No data available
Vapor Density: No data available
Relative Density: No data available
Solubility: Insoluble in water

Partition Coefficient: n-octanol/Water: No data available

Auto-Ignition Temp: No data available **Decomposition Temp:** No data available

Viscosity: No data available

10. Stability and Reactivity

Reactivity: Not normally reactive.

Chemical Stability: Stable under recommended conditions. **Possibility of Hazardous Reactions:** No data available.

Conditions to Avoid: Avoid heat, hot surfaces, sparks, open flames and

other sources of ignition.

Incompatible Materials: None known.

Hazardous Decomposition Products: Carbon monoxide and carbon

dioxide.

11. Toxicological Information

Eye Contact: Causes serious eye irritation.

Skin Contact: Causes skin irritation. May cause an allergic skin

reaction.

Inhalation: Harmful if inhaled. May cause respiratory irritation.

Ingestion: No data available.

Chronic Health Effects: May cause an allergic skin reaction.

Acute Toxicity Values: For Hexamethylene diisocyanate (CAS 28182-

81-2):

Oral LD_{50} (rat): >5,000 mg/kg Inhalation LC_{50} (rat): 4 mg/L, 4hr

Respiratory Sensitization: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Components are not classified as mutagens. **Carcinogenicity:** Components are not classified as carcinogens. **Reproductive Toxicity:** Components are not classified as reproductive

Specific Target Organ Toxicity: Causes respiratory irritation, drowsiness or dizziness.

12. Ecological Information

Ecotoxicity: Toxic to aquatic life with long lasting effects. Avoid

release to the environment.

Persistence and Degradability: No data available. Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. Disposal Considerations

Do not discharge into waterways. Dispose according to local, state, and federal regulations.

14. Transport Information



SAFETY DATA SHEET

DOT: UN1993, Flammable liquid, n.o.s. (acetone), 3, II. (LTD QTY if

shipped in quantities of 1L (0.3gal) or less.)

IATA/IMDG: UN1993, Flammable liquid, n.o.s. (acetone), 3, II **Emergency Shipping Information:** Call CHEMTREC, 800-424-9300 or

+1-703-527-3887

15. Regulatory Information

U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: The RQ for 1,6-hexamethylene diisocyanate is 100lb. Some states have more stringent reporting requirements.

SARA TITLE III Section 311/312: Acute/Chronic Health Hazard Section 313 Toxic Chemicals: This product does not contain chemicals subject to SARA Title III Section 313 Reporting requirements. Section 302 Extremely Hazardous Substances (TPQ): None EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on TSCA.

STATE REGULATIONS:

California Proposition 65: WARNING: This product can expose you to chemicals including methyloxirane and benzene which are known to the State of California to cause cancer and/or reproductive harm. www.P65Warnings.ca.gov

16. Other Information

Training Advice: All personnel using/handling this product should be trained in proper chemical handling and the need for and use of engineering controls and protective equipment.

Recommended Uses and Restrictions: This product is intended for industrial use only.

SDS Revision Notes: GHS Format: June 7, 2022

Disclaimer: The information contained herein is considered accurate; however, BDC Epoxy Systems, Inc. makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.